

J02380 JLM Diesel Turbo Cleaner

GCG Turbochargers Australia Pty Ltd

Chemwatch: 5680-13

Version No: 2.1

Safety Data Sheet according to Work Health and Safety Regulations (Hazardous Chemicals) 2023 and ADG requirements

Chemwatch Hazard Alert Code: 1

Issue Date: 12/06/2024

Print Date: 18/06/2024

S.GHS.AUS.EN.E

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	J02380 JLM Diesel Turbo Cleaner
Chemical Name	Not Applicable
Synonyms	Not Available
Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains 2-ethylhexyl nitrate)
Chemical formula	Not Applicable
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Fuel Additive. Use according to manufacturer's directions.
--------------------------	---

Details of the manufacturer or supplier of the safety data sheet

Registered company name	GCG Turbochargers Australia Pty Ltd
Address	117 Eldridge Road Condell Park NSW 2200 Australia
Telephone	+61291333855
Fax	Not Available
Website	www.jmlubricants.com.au
Email	sales@jmlubricants.com.au

Emergency telephone number

Association / Organisation	GCG Turbochargers Australia Pty Ltd	CHEMWATCH EMERGENCY RESPONSE (24/7)
Emergency telephone numbers	+61291333855	+61 1800 951 288
Other emergency telephone numbers	Not Available	+61 3 9573 3188

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

COMBUSTIBLE LIQUID, regulated for storage purposes only

Poisons Schedule	Not Applicable
Classification ^[1]	Flammable Liquids Category 4, Aspiration Hazard Category 1, Serious Eye Damage/Eye Irritation Category 2B, Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Category 3, Hazardous to the Aquatic Environment Long-Term Hazard Category 2
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

Label elements

Hazard pictogram(s)	
---------------------	---

Signal word	Danger
-------------	--------

Hazard statement(s)

H227	Combustible liquid.
H304	May be fatal if swallowed and enters airways.
H320	Causes eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
AUH066	Repeated exposure may cause skin dryness and cracking.

Precautionary statement(s) Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
------	--

P271	Use only outdoors or in a well-ventilated area.
P261	Avoid breathing mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves and protective clothing.
P264	Wash all exposed external body areas thoroughly after handling.

Precautionary statement(s) Response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider.
P331	Do NOT induce vomiting.
P370+P378	In case of fire: Use alcohol resistant foam or normal protein foam to extinguish.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P391	Collect spillage.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Precautionary statement(s) Storage

P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
------	--

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
1174522-09-8	50-100	hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics
27247-96-7	2.5-10	2-ethylhexyl nitrate
90622-58-5	<2.5	alkanes, C11-15-iso-
64742-94-5	<1	solvent naphtha petroleum, heavy aromatic
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; * EU IOELVs available	

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none">Wash out immediately with fresh running water.Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.Seek medical attention without delay; if pain persists or recurs seek medical attention.Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin contact occurs:</p> <ul style="list-style-type: none">Immediately remove all contaminated clothing, including footwear.Flush skin and hair with running water (and soap if available).Seek medical attention in event of irritation.
Inhalation	<ul style="list-style-type: none">If fumes or combustion products are inhaled remove from contaminated area.Lay patient down. Keep warm and rested.Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.Transport to hospital, or doctor.
Ingestion	<ul style="list-style-type: none">If swallowed do NOT induce vomiting.If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.Observe the patient carefully.Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.Seek medical advice.Avoid giving milk or oils.Avoid giving alcohol.If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

- ▶ Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.
- ▶ Water spray or fog - Large fires only.

Special hazards arising from the substrate or mixture

Fire Incompatibility	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
----------------------	--

Advice for firefighters

Fire Fighting	<ul style="list-style-type: none">▶ Alert Fire Brigade and tell them location and nature of hazard.▶ Wear full body protective clothing with breathing apparatus.▶ Prevent, by any means available, spillage from entering drains or water course.▶ Use water delivered as a fine spray to control fire and cool adjacent area.▶ Avoid spraying water onto liquid pools.▶ DO NOT approach containers suspected to be hot.▶ Cool fire exposed containers with water spray from a protected location.▶ If safe to do so, remove containers from path of fire.
Fire/Explosion Hazard	<ul style="list-style-type: none">▶ Combustible.▶ Slight fire hazard when exposed to heat or flame.▶ Heating may cause expansion or decomposition leading to violent rupture of containers.▶ On combustion, may emit toxic fumes of carbon monoxide (CO).▶ May emit acid smoke.▶ Mists containing combustible materials may be explosive. <p>Combustion products include: carbon dioxide (CO2) nitrogen oxides (NOx) other pyrolysis products typical of burning organic material.</p>
HAZCHEM	*3Z

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	<p>Environmental hazard - contain spillage.</p> <ul style="list-style-type: none">▶ Clean up all spills immediately.▶ Avoid breathing vapours and contact with skin and eyes.▶ Control personal contact with the substance, by using protective equipment.▶ Contain and absorb spill with sand, earth, inert material or vermiculite.▶ Wipe up.▶ Place in a suitable, labelled container for waste disposal.
Major Spills	<p>Environmental hazard - contain spillage. Moderate hazard.</p> <ul style="list-style-type: none">▶ Clear area of personnel and move upwind.▶ Alert Fire Brigade and tell them location and nature of hazard.▶ Wear breathing apparatus plus protective gloves.▶ Prevent, by any means available, spillage from entering drains or water course.▶ No smoking, naked lights or ignition sources.▶ Increase ventilation.▶ Stop leak if safe to do so.▶ Contain spill with sand, earth or vermiculite.▶ Collect recoverable product into labelled containers for recycling.▶ Absorb remaining product with sand, earth or vermiculite.▶ Collect solid residues and seal in labelled drums for disposal.▶ Wash area and prevent runoff into drains.▶ If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	<p>The conductivity of this material may make it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10 000 pS/m., Whether a liquid is nonconductive or semi-conductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid.</p> <ul style="list-style-type: none">▶ Containers, even those that have been emptied, may contain explosive vapours.▶ Do NOT cut, drill, grind, weld or perform similar operations on or near containers.▶ DO NOT allow clothing wet with material to stay in contact with skin• Electrostatic discharge may be generated during pumping - this may result in fire.• Ensure electrical continuity by bonding and grounding (earthing) all equipment.• Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (<=1 m/sec until fill pipe submerged to twice its diameter, then <= 7 m/sec).• Avoid splash filling.• Do NOT use compressed air for filling discharging or handling operations.• Wait 2 minutes after tank filling (for tanks such as those on road tanker vehicles) before opening hatches or manholes.• Wait 30 minutes after tank filling (for large storage tanks)
---------------	--

	<ul style="list-style-type: none">· before opening hatches or manholes. Even with proper· grounding and bonding, this material can still accumulate an· electrostatic charge. If sufficient charge is allowed to· accumulate, electrostatic discharge and ignition of flammable· air-vapour mixtures can occur. Be aware of handling· operations that may give rise to additional hazards that result· from the accumulation of static charges. These include but are· not limited to pumping (especially turbulent flow), mixing,· filtering, splash filling, cleaning and filling of tanks and· containers, sampling, switch loading, gauging, vacuum truck· operations, and mechanical movements. These activities may· lead to static discharge e.g. spark formation. Restrict line· velocity during pumping in order to avoid generation of· electrostatic discharge (= 1 m/s until fill pipe submerged to· twice its diameter, then = 7 m/s). Avoid splash filling.· Do NOT use compressed air for filling, discharging, or handling operations<ul style="list-style-type: none">▶ Avoid all personal contact, including inhalation.▶ Wear protective clothing when risk of exposure occurs.▶ Use in a well-ventilated area.▶ Prevent concentration in hollows and sumps.▶ DO NOT enter confined spaces until atmosphere has been checked.▶ Avoid smoking, naked lights or ignition sources.▶ Avoid contact with incompatible materials.▶ When handling, DO NOT eat, drink or smoke.▶ Keep containers securely sealed when not in use.▶ Avoid physical damage to containers.▶ Always wash hands with soap and water after handling.▶ Work clothes should be laundered separately.▶ Use good occupational work practice.▶ Observe manufacturer's storage and handling recommendations contained within this SDS.▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.
Other information	<ul style="list-style-type: none">▶ Store in original containers.▶ Keep containers securely sealed.▶ No smoking, naked lights or ignition sources.▶ Store in a cool, dry, well-ventilated area.▶ Store away from incompatible materials and foodstuff containers.▶ Protect containers against physical damage and check regularly for leaks.▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Suitable container	<ul style="list-style-type: none">▶ Metal can or drum▶ Packaging as recommended by manufacturer.▶ Check all containers are clearly labelled and free from leaks.
Storage incompatibility	<ul style="list-style-type: none">▶ Avoid reaction with oxidising agents

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
J02380 JLM Diesel Turbo Cleaner	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not Available	Not Available
2-ethylhexyl nitrate	Not Available	Not Available
alkanes, C11-15-iso-	Not Available	Not Available
solvent naphtha petroleum, heavy aromatic	Not Available	Not Available

Exposure controls

Appropriate engineering controls	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p> <p>Employers may need to use multiple types of controls to prevent employee overexposure.</p> <p>Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection. An approved self contained breathing apparatus (SCBA) may be required in some situations.</p> <p>Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.</p> <div>Type of Contaminant: <div>Air Speed:</div></div>
----------------------------------	---

J02380 JLM Diesel Turbo Cleaner

	<div>solvent, vapours, degreasing etc., evaporating from tank (in still air).</div> <div>aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)</div> <div>direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)</div> <div>grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).</div> <div>Within each range the appropriate value depends on:</div> <table><tr><td>Lower end of the range</td><td>Upper end of the range</td></tr><tr><td>1: Room air currents minimal or favourable to capture</td><td>1: Disturbing room air currents</td></tr><tr><td>2: Contaminants of low toxicity or of nuisance value only.</td><td>2: Contaminants of high toxicity</td></tr><tr><td>3: Intermittent, low production.</td><td>3: High production, heavy use</td></tr><tr><td>4: Large hood or large air mass in motion</td><td>4: Small hood-local control only</td></tr></table> <div>Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.</div>	Lower end of the range	Upper end of the range	1: Room air currents minimal or favourable to capture	1: Disturbing room air currents	2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity	3: Intermittent, low production.	3: High production, heavy use	4: Large hood or large air mass in motion	4: Small hood-local control only	<div>0.25-0.5 m/s (50-100 f/min.)</div> <div>0.5-1 m/s (100-200 f/min.)</div> <div>1-2.5 m/s (200-500 f/min.)</div> <div>2.5-10 m/s (500-2000 f/min.)</div>
Lower end of the range	Upper end of the range											
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents											
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity											
3: Intermittent, low production.	3: High production, heavy use											
4: Large hood or large air mass in motion	4: Small hood-local control only											
Individual protection measures, such as personal protective equipment	<div></div>											
Eye and face protection	<div><div><div>▶ Safety glasses with side shields.</div><div>▶ Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]</div><div>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].</div></div></div>											
Skin protection	See Hand protection below											
Hands/feet protection	<div><div><div>▶ Wear chemical protective gloves, e.g. PVC.</div><div>▶ Wear safety footwear or safety gumboots, e.g. Rubber</div></div><div>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</div><div>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</div><div>Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</div><div>Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:</div><div><div><div>- frequency and duration of contact,</div><div>- chemical resistance of glove material,</div><div>- glove thickness and</div><div>- dexterity</div></div></div><div>Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</div><div><div>- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</div><div>- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</div><div>- Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.</div><div>- Contaminated gloves should be replaced.</div></div><div>As defined in ASTM F-739-96 in any application, gloves are rated as:</div><div><div><div>- Excellent when breakthrough time > 480 min</div><div>- Good when breakthrough time > 20 min</div><div>- Fair when breakthrough time < 20 min</div><div>- Poor when glove material degrades</div></div></div><div>For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.</div><div>It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.</div><div>Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.</div><div>Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:</div><div><div><div>- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.</div><div>- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential</div></div></div><div>Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</div></div>											
Body protection	See Other protection below											
Other protection	<div><div><div>▶ Overalls.</div><div>▶ P.V.C apron.</div><div>▶ Barrier cream.</div><div>▶ Skin cleansing cream.</div><div>▶ Eye wash unit.</div></div></div>											

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	A-AUS / Class1 P2	-
up to 50	1000	-	A-AUS / Class 1 P2
up to 50	5000	Airline *	-
up to 100	5000	-	A-2 P2
up to 100	10000	-	A-3 P2
100+			Airline**

- * - Continuous Flow ** - Continuous-flow or positive pressure demand
A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)
- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
 - ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
 - ▶ Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Flammable amber / brown liquid with characteristic odor; dos not mix with water.		
Physical state	Liquid	Relative density (Water = 1)	0.81
Odour	Characteristic	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	>200
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	>7
Initial boiling point and boiling range (°C)	>150	Molecular weight (g/mol)	Not Available
Flash point (°C)	>62	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Combustible.	Oxidising properties	Not Available
Upper Explosive Limit (%)	7.0	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	0.6	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	0.1	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none">▶ Unstable in the presence of incompatible materials.▶ Product is considered stable.▶ Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	<p>Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.</p> <p>Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.</p> <p>There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.</p> <p>Inhalation hazard is increased at higher temperatures.</p> <p>Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.</p> <p>Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in</p>
---------	--

	respiratory depression and may be fatal.
Ingestion	Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733)
Skin Contact	Repeated exposure may cause skin cracking, flaking or drying following normal handling and use. There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. The liquid may be able to be mixed with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material is unlikely to produce an irritant dermatitis as described in EC Directives. The material may accentuate any pre-existing dermatitis condition
Eye	There is some evidence to suggest that this material can cause eye irritation and damage in some persons.
Chronic	Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following. There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

J02380 JLM Diesel Turbo Cleaner	TOXICITY	IRRITATION
	Not Available	Not Available
hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >=3160 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]
	Inhalation (Rat) LC50: >=6.1 mg/L4h ^[1]	Skin: no adverse effect observed (not irritating) ^[1]
	Oral (Rat) LD50: >5000 mg/kg ^[1]	
2-ethylhexyl nitrate	TOXICITY	IRRITATION
	dermal (rat) LD50: >4820 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]
	Inhalation (Rat) LC50: >1.15 mg/l4h ^[2]	Skin: no adverse effect observed (not irritating) ^[1]
	Oral (Rat) LD50: >2000 mg/kg ^[2]	
alkanes, C11-15-iso-	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >3200 mg/kg ^[2]	Not Available
	Inhalation (Rat) LC50: >5.01 mg/L4h ^[2]	
	Oral (Rat) LD50: >10000 mg/kg ^[2]	
solvent naphtha petroleum, heavy aromatic	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg ^[2]	Eye (rabbit): Irritating [PETROFIN]
	Inhalation (Rat) LC50: >0.003 mg/L4h ^[1]	Eye: adverse effect observed (irritating) ^[1]
	Oral (Rat) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]
		Skin: adverse effect observed (irritating) ^[1]
		Skin: no adverse effect observed (not irritating) ^[1]

Legend: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

HYDROCARBONS, C10-13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS	<p>Animal testing showed exposure to high concentrations (over 3500 parts per million) of C9 to C13 alkanes in air caused inco-ordination, seizures and spasms. Cerebellar damage was found on autopsy in some animals. It appears that exposure may possibly damage the central nervous system.</p> <p>For high molecular weight aliphatic hydrocarbons:</p> <p>Acute toxicity:</p> <p>Four studies were available for acute oral toxicity, dealing with the toxicity of C5-C20 normal paraffins, C14-C17 n-alkanes, C14-C16 paraffins and isohexadecane. All studies were conducted similarly to OECD guideline 401 without GLP compliance. All studies show no mortality at concentrations up to 5000 mg/kg bw.</p> <p>Three studies were available for acute dermal toxicity, dealing with the toxicity of C5-C20 normal paraffins, C14-C17 n-alkanes and C14-C16 paraffins. All studies were conducted similarly to OECD guideline 402 without GLP compliance. All studies show no mortality at concentrations equal to or higher than 2000 mg/kg bw.</p> <p>A reliable study and a non-reliable study were available for acute inhalation, dealing with the toxicity of hydrocarbons, C10-C12, isoalkanes, < 2% aromatics and C14-C16 n-paraffins, respectively. All studies were conducted similarly to OECD guideline 403. They all show no mortality at concentrations equal to or higher than 5000 mg/m3.</p> <p>Sensitisation:</p> <p>C9-C14 aliphatic, < 2% aromatic hydrocarbons fluids were determined not to be skin sensitizers using Magnusson and Kligman Guinea-Pig Maximization tests (OECD TG 406). C9-C14 aliphatic, <2% aromatic hydrocarbons fluids were determined not to be skin sensitizers in Human Repeated Insult Patch Tests (HRIPT)</p> <p>C10-12 isoalkanes (<2% aromatics), C11-C14 n-alkanes (<2% aromatics) and C10-C13 (<2% aromatics) were not dermal sensitizers using a Magnusson and Kligman Guinea-Pig Maximization test (OECD TG 406).</p> <p>However, skin sensitization studies utilizing C9-14 aliphatics (<2 % aromatics) found no indication of skin sensitization in guinea pigs. Additional studies on C14-C20 aliphatics (<2% aromatics) in humans also found no indication of skin sensitization.</p> <p>There are no reports of respiratory sensitization from C14-20 aliphatics (<2 % aromatics) in laboratory animals or humans.</p> <p>Repeat dose toxicity:</p> <p>Oral: C9-C14 aliphatic, < 2% aromatic hydrocarbon fluids are expected to have a low order of repeated dose toxicity by the oral route of exposure. All tests were performed in a manner similar or equivalent to currently established OECD guidelines. In a repeated dose study where C9-C14 aliphatic, < 2% aromatic hydrocarbon fluids were administered via oral gavage, no signs of toxicity were observed at the maximum experimental dose tested, 5000 mg/kg/day.</p>
---	--

J02380 JLM Diesel Turbo Cleaner

Inhalation: In a repeated dose study where C9-C14 aliphatic, < 2% aromatic hydrocarbon fluids were administered via inhalation, no signs of toxicity were observed at 10400 mg/m3. Based on these observations, the repeat inhalation concentration NOAEL is ≥ 10400 mg/m3 (10.4 mg/L) for C9-C14 aliphatic, < 2% aromatic hydrocarbon fluids.

Two read-across studies from the structurally analogous test materials "hydrocarbons C12-C16, n-alkanes, isoalkanes, cyclics, <2% aromatics" and "hydrocarbons, C10 -C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics" were analysed. All tests were performed in a manner similar or equivalent to currently established OECD guidelines. The systemic NOAEL were determined to be higher than 1000 and 5000 mg/kg/day, respectively.

Inhalation: a repeated inhalation toxicity study was performed with "Hydrocarbons, C10 – C12, isoalkanes, < 2% aromatics" similarly to OECD guideline 413. Albino rats were exposed for 6 hours/day, 5 days/week for 13 weeks at nominal vapour concentrations of 10400 mg/m3, 5200 mg/m3, and 2600 mg/m3 to assess inhalation toxicity. As there were no pathologic changes, changes in organ weights were judged to have been compensatory rather than toxic effects. Based on these results, the No Observed Adverse Effect Concentration (NOAEC) was greater than or equal to 10400 mg/m3.

Oral: C9-C14 aliphatic, < 2% aromatic hydrocarbon fluids are expected to have a low order of repeated dose toxicity by the oral route of exposure. All tests were performed in a manner similar or equivalent to currently established OECD guidelines. In a repeated dose study where C9-C14 aliphatic, < 2% aromatic hydrocarbon fluids were administered via oral gavage, no signs of toxicity were observed at the maximum experimental dose tested, 5000 mg/kg/day.

Inhalation: In a repeated dose study where C9-C14 aliphatic, < 2% aromatic hydrocarbon fluids were administered via inhalation, no signs of toxicity were observed at 10400 mg/m3. Based on these observations, the repeat inhalation concentration NOAEL is ≥ 10400 mg/m3 (10.4 mg/L) for C9-C14 aliphatic, < 2% aromatic hydrocarbon fluids.

Genetic toxicity:

C9-C14 aliphatic, < 2% aromatic hydrocarbons fluids are not mutagenic using in vitro or in vivo genotoxicity assays. In bacterial tests, C9-C14 aliphatic, < 2% aromatic hydrocarbons fluids were not mutagenic in Salmonella strains tested in the presence or absence of metabolic activation. C9 -C14 aliphatic, <2% aromatic hydrocarbon fluids were negative in a in vitro mammalian cell gene mutation assay. In sister chromatid exchange and in chromosomal aberration studies, C9-C14 aliphatic, < 2% aromatic hydrocarbons fluids did not produce an effect. C9-C14 aliphatic, < 2% aromatic hydrocarbons fluids were also non-mutagenic when tested in an in vivo mouse bone marrow micronucleus assay and when tested in dominant lethal studies utilizing an inhalation route of exposure. All studies were conducted in a manner similar or equivalent to currently established OECD guidelines. C9-C14 aliphatic, < 2% aromatic hydrocarbons fluids are a non-genotoxic agent and classification is not warranted under the new Regulation (EC) 1272/2008 on classification, labeling and packaging of substances and mixtures (CLP) or under the Directive 67/518/EEC for dangerous substances and Directive 1999/45/EC for preparations.

All Ames tests on "hydrocarbons, C14-C20, n-alkanes, isoalkanes, cyclics, <2% aromatics" showed no mutagenic effect with and without metabolic activation. The chromosome aberration study in CHO cells on "hydrocarbons, C12-C16, n-alkanes, isoalkanes, cyclics, <2% aromatics" also showed no signs of mutagenicity. A mouse lymphoma forward mutation assay performed with hydrodesulfurised kerosene also showed no mutagenic properties.

The weight of evidence is derived from study records reported for the C9-C14 aliphatic, <2% aromatics. C9-C14 aliphatic, <2% aromatics are not genotoxic and are not classifiable as mutagens based upon the results of reliable in vitro and in vivo studies. In bacterial reverse mutation studies, the C9-C14 aliphatic, <2% aromatics were not mutagenic in the presence or absence of metabolic activation (IUCLID section 7.6.1). In mammalian cells in vitro, and in rats in vivo there were no mutagenic, clastogenic or aneugenic effects reported in read-across from studies on C9-C14 aliphatic, <2% aromatics: a negative chromosome aberration (Human Peripheral Lymphocyte Chromosomal Aberration Test, Chinese Hamster Ovary Sister Chromatid Exchange Assay); and an in vivo inhalation exposure bone marrow chromosomal aberration study and micronucleus test (IUCLID sections 7.6.1 and 7.6.2).

Endpoint Conclusion: No adverse effect observed (negative)

Toxicity to reproduction:

C9-C14 aliphatic, <2% aromatic hydrocarbon fluids were examined for reproductive toxicity in a 28 day combined repeated dose toxicity study with the reproduction / developmental toxicity screening test (OECD TG 422). C9-C14 aliphatic, <2% aromatic hydrocarbon fluids were administered oral gavage at a dose of 0, 25, 150, or 1000 mg/kg/day to groups of Sprague-Dawley rats. It was concluded that C9-C14 aliphatic, <2% aromatic hydrocarbon fluids did not induce reproductive toxicity in the parental animals and no effects on the endocrine system were observed. Therefore, the NOAEL was determined to be ≥ 1000 mg/kg bw/day.

C9-C14 aliphatic, <2% aromatic hydrocarbon fluids were examined in a reproduction / developmental toxicity screening test (OECD TG 421). C9-C14 aliphatic, <2% aromatic hydrocarbon fluids were administered by oral gavage at a dose of 0 (vehicle), 100, 300, 1000 mg/kg/day to groups of Sprague-Dawley rats. It was concluded that C9-C14 aliphatic, <2% aromatic hydrocarbon fluids did not induce reproductive toxicity in the parental animals and no effects on the endocrine system were observed. Therefore, the NOAEL was determined to be ≥ 1000 mg/kg bw/day.

Based on this study and the lack of systemic toxicity, C9-C14 aliphatic, <2% aromatic hydrocarbon fluids, are not expected to be reproductive toxicants.

In bacterial reverse mutation studies, the C14-C20 aliphatic, <2% aromatics were not mutagenic in the presence or absence of metabolic activation (IUCLID section 7.6.1). In mammalian cells in vitro, and in rats in vivo there were no mutagenic, clastogenic or aneugenic effects reported in read-across from studies on hydrodesulfurized kerosene kerosene, and jet fuels that included: a negative chromosome aberration (Human Peripheral Lymphocyte Chromosomal Aberration Test, Chinese Hamster Ovary Sister Chromatid Exchange Assay); and an in vivo inhalation exposure bone marrow chromosomal aberration study and micronucleus test in rats and mice (IUCLID sections 7.6.1 and 7.6.2).

C9-C14 aliphatic, < 2% aromatic hydrocarbon fluids were examined for reproductive toxicity in a 28 day combined repeated dose toxicity study with the reproduction / developmental toxicity screening test (OECD TG 422). C9-C14 aliphatic, < 2% aromatic hydrocarbon fluids were administered oral gavage at a dose of 0, 25, 150, or 1000 mg/kg/day to groups of Sprague-Dawley rats. It was concluded that C9-C14 aliphatic, < 2% aromatic hydrocarbon fluids did not induce reproductive toxicity in the parental animals and no effects on the endocrine system were observed. Therefore, the NOAEL was determined to be ≥ 1000 mg/kg bw/day.

Exposure in humans:

Seven studies were available on the irritation and/or sensitisation potential of several types of hydrocarbon solvents in volunteers. Clinical tests were conducted with populations ranging from 29 to 112 patients. None of the test substances elicited any sensitisation and/or irritation effects except C5-C20 paraffin, which showed a cumulative irritation effect at 75% . However, this substance was tested under occlusive patch, a condition which exacerbates the irritancy of hydrocarbon solvents.

Toxicokinetics:

If C9-C14 aliphatic, <2% aromatic hydrocarbon fluids are absorbed, they are typically metabolized by side chain oxidation to alcohol and carboxylic acid derivatives. These metabolites can be glucuronidated and excreted in the urine or further metabolized before being excreted. The majority of the metabolites are excreted in the urine and to a lower extent, in the faeces. Excretion is rapid with the majority of the elimination occurring within the first 24 hours of exposure. As a result of the lack of systemic toxicity and the ability of the parent material to undergo metabolism and rapid excretion, bioaccumulation of the test substance in the tissues is not likely to occur.

C9-C14 aliphatic, <2% aromatic hydrocarbon fluids are poorly absorbed dermally with an estimated overall percutaneous absorption rate of approximately 2ug/cm2/hr or 1% of the total applied fluid. Regardless of exposure route, C9-C14 aliphatic, <2% aromatic hydrocarbon fluids are rapidly metabolized and eliminated.

C14-C20 aliphatic, <2% aromatic hydrocarbon fluids are typically metabolized by side chain oxidation to alcohol and carboxylic acid derivatives. These metabolites can be glucuronidated and excreted in the urine or further metabolized before being excreted. The majority of the metabolites are excreted in the urine and to a lower extent, in the faeces. Excretion is rapid with the majority of the elimination occurring within the first 24 hours of exposure. As a result of the lack of systemic toxicity and the ability of the parent material to undergo metabolism and rapid excretion, bioaccumulation of the test substance in the tissues is not likely to occur.

Short description of key information on absorption rate:

C14-C20 aliphatic, <2% aromatic hydrocarbon fluids can be dermally absorbed, although they tend to partition into the stratum corneum.

When dermally absorbed, C14-C20 aliphatic, <2% aromatic hydrocarbon fluids are rapidly metabolized and eliminated.

Approximately 34% of C14–C20 aliphatic, <2% aromatic hydrocarbon fluids are absorbed when ingested. C14–C20 aliphatic, <2% aromatic hydrocarbon fluids are poorly dermally absorbed. Absorption following inhalation is assumed to be similar to ingestion since exposures will be to aerosol. Regardless of exposure route, C14–C20 aliphatic, <2% aromatic hydrocarbon fluids are rapidly metabolized. Bioaccumulation of C14–C20 aliphatic, <2% aromatic hydrocarbon fluids is not expected.

C14-C20 aliphatic, <2% aromatic hydrocarbon fluids are absorbed if ingested. C14-C20 aliphatic, <2% aromatic hydrocarbon fluids undergo metabolism and rapid excretion and low deposition, bioaccumulation of the test substance in the tissues is not likely to occur.

J02380 JLM Diesel Turbo Cleaner

	<p>The fate of pristane (2,6,10,14-tetramethylpentadecane) was studied in rats after a single per os administration of 3H-labeled pristane. The balance study showed extensive fecal excretion (66%) mainly as unchanged hydrocarbon, whereas about 14% of ingested pristane was excreted in urine as pristane metabolites and tritiated water. After one week, 8.3% of the ingested 3H still was stored in the carcass and the radioactive distribution in tissues and organs showed a preferential incorporation into adipose tissue and liver. Over 75% of the radioactivity stored in the carcass was associated with pristane metabolites and tritiated water. Tissue metabolites were characterized by thin layer chromatography, gas chromatography, and mass spectrometric analyses. Four metabolites were identified: pristan-1-ol, pristane-2-ol, pristanic acid and 4,8,12-trimethyltridecanoic acid. These results demonstrated that pristane undergoes subterminal hydroxylation or terminal oxidation followed by the classical beta-oxidation process.</p> <p>Labeled paraffins with 8-18 C atoms prepared from unsaturated hydrocarbons by addition of deuterium have been added in oily solution to normal rats food. After six days an increase of deuterium content in the body fluid of all the rats was observed indicating that the labeled compounds had been metabolized. Deuterium was found in the fatty acids of the body fats and the liver lipids especially after feeding octadecane and hexadecane. Isolating oleic, stearic, and palmitic acids containing deuterium, indicated that methyl- and beta-oxidation of these hydrocarbons has occurred. Fatty acids resulting from the metabolism of hydrocarbons with shorter chains were not deposited but in these cases the urine contained fatty acids with higher deuterium content than after administration of octadecane and hexadecane. According to the deuterium content of the neutral fractions from the liver and body lipids all the hydrocarbons tested were deposited only to a small extent, the largest depots occurring mainly after feeding with octadecane and hexadecane.</p> <p>Discussion on absorption rate:</p> <p>There have not been any in vivo dermal absorption studies of C14 – C20 aliphatic, <2% aromatic hydrocarbon fluids, but there have been in vitro studies of similar constituents, particularly hexadecane.</p> <p>The percutaneous absorption and cutaneous disposition of topically applied neat Jet-A, JP-8, and JP-8(100) jet fuels (25 µL/5 cm²) was examined by monitoring the absorptive flux of the marker components 14C naphthalene and 4H dodecane simultaneously applied non-occluded to isolated perfused porcine skin flaps (a = 4). Absorption of 14C hexadecane was estimated from JP-8 fuel. Absorption and disposition of naphthalene and dodecane were also monitored using a nonvolatile JP-8 fraction reflecting exposure to residual fuel that might occur 24 h after a jet fuel spill. In all studies, perfusate, stratum corneum, and skin concentrations were measured over 5 h. Naphthalene absorption had a clear peak absorptive flux at less than 1 h, while dodecane and hexadecane had prolonged, albeit significantly lower, absorption flux profiles. Within JP-8, absorption was (mean +/- SEM; % dose) hexadecane (0.18 +/- 0.08). The area under the curve (AUC) was determined to be (mean +/- SEM; % dose-h/mL): hexadecane (0.0017 +/- 0.0003).</p> <p>The flux, permeability coefficient (Kp), and binding of hexadecane for porcine skin was determined to be 8.80 +/- 0.00 (nmol/cm²/h) x 10E-3. The permeability coefficient (Kp), and binding of hexadecane for human skin were determined to be 7.02 +/- 0.00 (nmol/cm²/h) x 10E-3. Factor of difference (FOD) in the permeability of pig and human skin was 1.28 for hexadecane. The FOD in binding of hexadecane to pig and human skin was found to be 0.76.</p> <p>Over view of percutaneous absorption of hydrocarbon solvents</p> <p>There are no studies of repeated dose toxicity of hydrocarbon solvents using the dermal route of administration. Accordingly, where it is necessary to calculate dermal DNELs, systemic data from studies utilizing other routes of administration, normally inhalation but also oral data, can be used in some situations. In accordance with ECHA guidance, read across from oral or inhalation data to dermal should account for differences in absorption where these exist. In fact, hydrocarbon solvents are poorly absorbed in most situations, in part because some are volatile and do not remain in contact with the skin for long periods of time and also because, due to their hydrophobic natures, do not partition well into aqueous environments and are poorly absorbed into the blood.</p> <p>If these differences in relative absorption are introduced into the DNEL calculations to calculate external doses, the DNELs based on systemic effects are highly inflated. This seems potentially misleading as it implies that substances have different intrinsic hazards when encountered by different routes whereas in fact the differences are due ultimately to differences in absorbed dose. .</p> <p>Several authors have assessed the percutaneous absorption of higher molecular weight aliphatic constituents. Using porcine skin models the percutaneous absorption values for aliphatic constituents ranging from nonane to tetradecane were well below 1 µg/cm²/hr. Rat and human skin are considered to be more permeable than human skin (so these numbers can be considered conservative.</p> <p>Results of percutaneous absorption studies with human skin under in vivo conditions produced values ranging from 1 – 2 µg/kg/day for decane, undecane and dodecane.</p> <p>With respect to aromatic hydrocarbons, most of the reported percutaneous absorption values) are less than 2 µg/cm²/day.</p> <p>After considering all of the above, it seems reasonable to assume apparent that across the entire range of hydrocarbon solvent constituents, percutaneous absorption values are less than 2 µg/cm²/day. Accordingly, when systemic dermal DNELs are calculated using route to route extrapolations, the values will not be corrected for differences in absorption. Rather, 2 µg/cm²/hr should be used as a common percutaneous absorption rate for all hydrocarbon solvents for which dermal exposure estimates are provided.</p>
2-ETHYLHEXYL NITRATE	Chemical with the aliphatic nitro group (-C-NO ₂) have been added to a list of DNA-reactive subgroups recognised by the National Toxicological Program (NTP, U.S. Dept Health and Human Services) for possible carcinogenic activity.
ALKANES, C11-15-ISO-	<p>for C10 - C12 isoalkanes:</p> <p>The safety of isoparaffins as used in cosmetic products was reviewed by the Cosmetic Ingredient Review (CIR) Expert Panel. These ingredients function mostly as solvents and also function as emollients in the 0001% to 90% concentration range. The CIR Expert Panel has reviewed relevant animal and clinical data and concluded that these ingredients are safe in the present practices of use and concentration</p> <p>The CIR Expert Panel noted that most of the available data related to oral or inhalation exposure to isoparaffins, but the dermal and ocular exposure data that were available, suggested mild ocular irritation, mild-to-severe irritation, no sensitization or photosensitization, and no phototoxicity. No significant toxicity was identified in oral or inhalation exposure studies of the following end points: genotoxicity, reproductive and developmental toxicity, or carcinogenicity. Nephrotoxicity, however, was a concern. The Expert Panel noted the involvement of a2u-globulin in the mechanism for isoparaffin-induced nephrotoxicity/renal tubule cell proliferation in male rats of various strains in oral and inhalation exposure studies. Humans lack this protein and, thus, the Panel agreed that findings associated with the a2u-globulin protein in male rats were not relevant to humans. This view was consistent with the US EPA position that it was not possible for the agency to derive an oral RfD for chronic oral exposure or a reference concentration for chronic inhalation exposure to isooctane because the available studies were limited, in that they were designed to only investigate the endpoints specific to a2u-globulin-associated nephropathy. The EPA also concluded that there was inadequate evidence to assess the carcinogenic potential of isooctane, based on the absence of human epidemiological studies and chronic bioassays on this compound. However, the CIR Expert Panel noted that no significant tumor incidence was found following life-time dermal application of petrolatum (15% in isooctane) to mice and also found no evidence of any concern regarding carcinogenic potential from exposure to isoparaffins as used in cosmetics.</p> <p>The potential adverse effects of inhaled aerosols depend on the specific chemical species, the concentration and the duration of the exposure and their site of deposition within the respiratory system. In practice, aerosols should have at least 99% of their particle diameters in the 10 to 110 mm range and the mean particle diameter in a typical aerosol spray has been reported as ~38 mm. Particles with an aerodynamic diameter of <10 mm are respirable. After reviewing the positive acute and subchronic inhalation toxicity data the Expert Panel determined that isoparaffins can be used safely in hair sprays, because the product particle size is not respirable.</p> <p>International Journal of Toxicology 31 (Supplement 3) 269S-295S 2012</p>
SOLVENT NAPHTHA PETROLEUM, HEAVY AROMATIC	<p>Petroleum contains aromatic (benzene, toluene, ethyl benzene, naphthalene) and aliphatic hydrocarbons (n-hexane), which can result in many detrimental health effects, including, cancer, tumour formation, hearing loss, and nervous system toxicity.</p> <p>Animal testing shows breathing in petroleum causes tumours of the liver and kidney; these are however not considered to be relevant in humans. Similarly, exposure to gasoline over a lifetime can cause kidney cancer in animals, but the relevance in humans is questionable. Most studies involving gasoline have shown that gasoline does not cause genetic mutation, including all recent studies in living human subjects (such as in petrol service station attendants).</p> <p>Animal studies show concentrations of toluene (>0.1%) can cause developmental effects such as lower birth weight and developmental toxicity to the nervous system of the foetus. Other studies show no adverse effects on the foetus.</p> <p>Prolonged contact with petroleum may result in skin inflammation and make the skin more sensitive to irritation and penetration by other materials.</p>
HYDROCARBONS, C10-13, N- ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS & ALKANES, C11-15-ISO- & SOLVENT NAPHTHA	<p>Animal studies indicate that normal, branched and cyclic paraffins are absorbed from the gastrointestinal tract and that the absorption of n-paraffins is inversely proportional to the carbon chain length, with little absorption above C30. With respect to the carbon chain lengths likely to be present in mineral oil, n-paraffins may be absorbed to a greater extent than iso- or cyclo-paraffins.</p> <p>The major classes of hydrocarbons are well absorbed into the gastrointestinal tract in various species. In many cases, the hydrophobic hydrocarbons are ingested in association with fats in the diet. Some hydrocarbons may appear unchanged as in the lipoprotein particles in</p>

Continued...

PETROLEUM, HEAVY AROMATIC	the gut lymph, but most hydrocarbons partly separate from fats and undergo metabolism in the gut cell. The gut cell may play a major role in determining the proportion of hydrocarbon that becomes available to be deposited unchanged in peripheral tissues such as in the body fat stores or the liver.			
Acute Toxicity	✗	Carcinogenicity	✗	
Skin Irritation/Corrosion	✗	Reproductivity	✗	
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓	
Respiratory or Skin sensitisation	✗	STOT - Repeated Exposure	✗	
Mutagenicity	✗	Aspiration Hazard	✓	
Legend: ✗ – Data either not available or does not fill the criteria for classification ✓ – Data available to make classification				

SECTION 12 Ecological information

Toxicity					
J02380 JLM Diesel Turbo Cleaner	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	>100mg/l	2
	NOEC(ECx)	48h	Crustacea	100mg/l	2
2-ethylhexyl nitrate	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	72h	Algae or other aquatic plants	0.46mg/l	2
	LC50	96h	Fish	2mg/l	2
	EC50	72h	Algae or other aquatic plants	1.18mg/l	2
	EC50	48h	Crustacea	0.83mg/l	2
alkanes, C11-15-iso-	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50(ECx)	48h	Crustacea	<100mg/l	1
	EC50	48h	Crustacea	<100mg/l	1
solvent naphtha petroleum, heavy aromatic	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96h	Fish	2-5mg/l	Not Available
	EC50(ECx)	48h	Crustacea	0.95mg/l	1
	EC50	72h	Algae or other aquatic plants	<1mg/l	1
	EC50	96h	Algae or other aquatic plants	11.7mg/l	2
	EC50	48h	Crustacea	0.95mg/l	1
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

Ingredient	Bioaccumulation
alkanes, C11-15-iso-	HIGH (BCF = 100000)
solvent naphtha petroleum, heavy aromatic	LOW (BCF = 159)

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal	Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate: ▶ Reduction
------------------------------	---

- Reuse

► Recycling

► Disposal (if all else fails)
- This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

► **DO NOT allow wash water from cleaning or process equipment to enter drains.**

► It may be necessary to collect all wash water for treatment before disposal.

► In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.

► Where in doubt contact the responsible authority.

► Recycle wherever possible or consult manufacturer for recycling options.



► Consult State Land Waste Authority for disposal.

► Bury or incinerate residue at an approved site.

► Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 Transport information

Labels Required

	
Marine Pollutant	
HAZCHEM	•3Z

Land transport (ADG)

14.1. UN number or ID number	3082	
14.2. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains 2-ethylhexyl nitrate)	
14.3. Transport hazard class(es)	Class	9
	Subsidiary Hazard	Not Applicable
14.4. Packing group	III	
14.5. Environmental hazard	Environmentally hazardous	
14.6. Special precautions for user	Special provisions	274 331 335 375 AU01
	Limited quantity	5 L

Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082 are not subject to this Code when transported by road or rail in;

(a) packagings;

(b) IBCs; or

(c) any other receptacle not exceeding 500 kg(L).

- Australian Special Provisions (SP AU01) - ADG Code 7th Ed.

Air transport (ICAO-IATA / DGR)

14.1. UN number	3082	
14.2. UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (contains 2-ethylhexyl nitrate)	
14.3. Transport hazard class(es)	ICAO/IATA Class	9
	ICAO / IATA Subsidiary Hazard	Not Applicable
	ERG Code	9L
14.4. Packing group	III	
14.5. Environmental hazard	Environmentally hazardous	
14.6. Special precautions for user	Special provisions	A97 A158 A197 A215
	Cargo Only Packing Instructions	964
	Cargo Only Maximum Qty / Pack	450 L
	Passenger and Cargo Packing Instructions	964
	Passenger and Cargo Maximum Qty / Pack	450 L
	Passenger and Cargo Limited Quantity Packing Instructions	Y964
	Passenger and Cargo Limited Maximum Qty / Pack	30 kg G

Sea transport (IMDG-Code / GGVSee)

14.1. UN number	3082	
14.2. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains 2-ethylhexyl nitrate)	

14.3. Transport hazard class(es)	IMDG Class	9
	IMDG Subsidiary Hazard	Not Applicable
14.4. Packing group	III	
14.5. Environmental hazard	Marine Pollutant	
14.6. Special precautions for user	EMS Number	F-A , S-F
	Special provisions	274 335 969
	Limited Quantities	5 L

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code
Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not Available
2-ethylhexyl nitrate	Not Available
alkanes, C11-15-iso-	Not Available
solvent naphtha petroleum, heavy aromatic	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not Available
2-ethylhexyl nitrate	Not Available
alkanes, C11-15-iso-	Not Available
solvent naphtha petroleum, heavy aromatic	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics is found on the following regulatory lists
Not Applicable

2-ethylhexyl nitrate is found on the following regulatory lists
Australian Inventory of Industrial Chemicals (AIIC)
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2A: Probably carcinogenic to humans

alkanes, C11-15-iso- is found on the following regulatory lists
Australian Inventory of Industrial Chemicals (AIIC)
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

solvent naphtha petroleum, heavy aromatic is found on the following regulatory lists
Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
Australian Inventory of Industrial Chemicals (AIIC)
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

Additional Regulatory Information
Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	No (hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics)
Canada - DSL	No (hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics; alkanes, C11-15-iso-)
Canada - NDSL	No (hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics; 2-ethylhexyl nitrate; alkanes, C11-15-iso-; solvent naphtha petroleum, heavy aromatic)
China - IECSC	No (hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics)
Europe - EINEC / ELINCS / NLP	No (hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics)
Japan - ENCS	No (hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics)
Korea - KECI	No (hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics)
New Zealand - NZIoC	No (hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics)
Philippines - PICCS	No (hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics)
USA - TSCA	No (hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics; alkanes, C11-15-iso-)

National Inventory	Status
Taiwan - TCSI	No (hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics)
Mexico - INSQ	No (hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics; 2-ethylhexyl nitrate)
Vietnam - NCI	No (hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics)
Russia - FBEPH	No (hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics)
Legend:	<p>Yes = All CAS declared ingredients are on the inventory</p> <p>No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.</p>

SECTION 16 Other information

Revision Date	12/06/2024
Initial Date	12/06/2024

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

- ▶ PC - TWA: Permissible Concentration-Time Weighted Average
- ▶ PC - STEL: Permissible Concentration-Short Term Exposure Limit
- ▶ IARC: International Agency for Research on Cancer
- ▶ ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit
- ▶ TEEL: Temporary Emergency Exposure Limit
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations
- ▶ ES: Exposure Standard
- ▶ OSF: Odour Safety Factor
- ▶ NOAEL: No Observed Adverse Effect Level
- ▶ LOAEL: Lowest Observed Adverse Effect Level
- ▶ TLV: Threshold Limit Value
- ▶ LOD: Limit Of Detection
- ▶ OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- ▶ DNEL: Derived No-Effect Level
- ▶ PNEC: Predicted no-effect concentration

- ▶ AIIC: Australian Inventory of Industrial Chemicals
- ▶ DSL: Domestic Substances List
- ▶ NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European Inventory of Existing Commercial chemical Substances
- ▶ ELINCS: European List of Notified Chemical Substances
- ▶ NLP: No-Longer Polymers
- ▶ ENCS: Existing and New Chemical Substances Inventory
- ▶ KECI: Korea Existing Chemicals Inventory
- ▶ NZIoC: New Zealand Inventory of Chemicals
- ▶ PICCS: Philippine Inventory of Chemicals and Chemical Substances
- ▶ TSCA: Toxic Substances Control Act
- ▶ TCSI: Taiwan Chemical Substance Inventory
- ▶ INSQ: Inventario Nacional de Sustancias Químicas
- ▶ NCI: National Chemical Inventory
- ▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.

J02380 JLM Diesel Turbo Cleaner